

MODEL	FUEL	MODEL YEAR	FILLING QUANTITY	SPECIFICATIONS APPROVED OIL TYPES	RAVENOL PRODUCT	RECOMMENDATION	ALTERNATIVES TO THE RAVENOL PRODUCT
X-type 2.0 V6	Petrol	'01-'05	5,8	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
X-type 2.5, 3.0 V6	Petrol	'01-'06	5,8	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
X-type 2.5, 3.0 V6	Petrol	'06-'10	5,8	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
S-type V6, V8, type R	Petrol	'99-'07	6,3-6,9	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
XE 2.0	Petrol	'15-	5,4	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XE 3.0 V6, AWD	Petrol	'15-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XF 2.0	Petrol	'12-'15	5,4	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XF 2.0 GTDi	Petrol	'15-	5,4	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XF 3.0 V6, 4.2 V8, 4.2 V8 SC	Petrol	'08-'09	6-6,5	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
XF 3.0 V6, 4.2 V8 SC	Petrol	'09-'10	6,5	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
XF 3.0 V6	Petrol	'10-'12	6,5	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XF 3.0 V6 SC, 4WD	Petrol	'12-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
XF 3.0 V6 SC, 4WD	Petrol	'15-'15	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XF 3.0 V6	Petrol	'15-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XF 3.0 V6, AWD	Petrol	'15-	6,5	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XF 4.2 V8, 4.2 V8 SC	Petrol	'08-'09	6	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XF 4.2 V8 SC	Petrol	'09-'10	6	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XF 5.0 V8	Petrol	'09-'12	7,25	M2C925-A	RAVENOL SFE SAE 5W-20		
XF-, XFR 5.0 V8 SC	Petrol	'09-'12	7,25	M2C925-A	RAVENOL SFE SAE 5W-20		
XF-, XFR 5.0 V8 SC	Petrol	'12-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
XF-, XFR 5.0 V8 SC	Petrol	'15-'15	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XJ 6 3.2, 4.0, Sovereign, Sports	Petrol	'94-'97	8		RAVENOL TSI SAE 10W-40		RAVENOL HVE SAE 10W-50
XJR 4.0, SC	Petrol	'89-'97	8		RAVENOL TSI SAE 10W-40		

RAVENOL ECS SAE 0W-20

API SN/RCI ACEA A1/B1
Fully synthetic low friction motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, Resource Conserving, Ford WSS-M2C947-A, GM 6094M, Honda/Acura HTO-6, Chrysler MS-6395, Mitsubishi, Nissan, Mazda, Suzuki, Toyota, Jaguar Land Rover STJLR.51.5122

Art.Nr.: 1111102

RAVENOL VSF SAE 0W-30

ACEA C2
RAVENOL VSF SAE 0W-30 is a fully synthetic low friction engine oil based on PAD (Poly alpha olefines) with ClearSynto® technology for car diesel engines with and without turbocharging and direct injection. Minimizing friction, wear and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to the manufacturer's instructions.

Ford WSS-M2C950-A

Art.Nr.: 1111107

RAVENOL SFE SAE 5W-20

API SN/RCI
Fully synthetic low friction low SAPS motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, FORD WSS-M2C930-A, FORD WSS-M2C930-B (extended drain capability), Ford WSS-M2C925-A/B, Ford WSS-M2C948-B, Chrysler MS-6395, Honda/Acura HTO-6, Nissan, Mazda, Suzuki, Toyota, Fiat 9.55535-0R1, JaguarLandRover STJLR.03.5004

Art.Nr.: 1111110

RAVENOL FDS SAE 5W-30

API SL/CF ACEA A1/B1, A5/B5
Fully synthetic, low friction motor oil with ClearSynto® Technology for petrol and diesel passenger cars with and without turbocharging and direct injection.

Renault RN0700, FORD WSS-M2C913-D (fulfills FORD WSS-M2C913-A/B/C), Fiat 9.55535-G1, JAGUAR LAND ROVER STJLR.03.5003

Art.Nr.: 1111139

RAVENOL FLJ SAE 5W-30

ACEA C1
Synthetic, low SAPS, low-viscosity motor oil with ClearSynto® technology that is suitable for petrol and diesel cars, with or without turbochargers and fuel injectors. It minimises friction, deterioration and fuel consumption, as well as possessing excellent cold-start characteristics and a lengthened oil change interval.

JAGUAR LAND ROVER STJLR.03.5005, FORD WSS-M2C934-B, MAZDA, Mitsubishi

Art.Nr.: 1111143

MODEL	FUEL	MODEL YEAR	FILLING QUANTITY	SPECIFICATIONS APPROVED OIL TYPES	RAVENOL PRODUCT	RECOMMENDATION	ALTERNATIVES TO THE RAVENOL PRODUCT
XJR V8 4.0	Petrol	'97-'03	7,5		RAVENOL SSO SAE 0W-30		RAVENOL SSL SAE 0W-40
XJ12 6.0	Petrol	'94-'97	10		RAVENOL TSI SAE 10W-40		RAVENOL HVE SAE 10W-50
XJ-S 4.0	Petrol	'93-'96	8		RAVENOL TSI SAE 10W-40		RAVENOL HVE SAE 10W-50
XJ-S 6.0 V12	Petrol	'94-'96	10		RAVENOL TSI SAE 10W-40		RAVENOL HVE SAE 10W-50
XJ 6 3.0	Petrol	'03-'06	6,5	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XJ 6 3.0	Petrol	'06-'09	6,5	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XJ 8 3.2, 4.0	Petrol	'97-'03	7,5	ACEA A3	RAVENOL SSO SAE 0W-30	ACEA A3	RAVENOL SSL SAE 0W-40
XJ 8 3.5, 4.2, 4.2 SC	Petrol	'03-'06	6	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XJ 8 3.5, 4.2, 4.2 SC	Petrol	'06-'09	6	ACEA A3	RAVENOL SSO SAE 0W-30	M2C913-B	RAVENOL FDS SAE 5W-30
XJ 2.0	Petrol	'12-'15	5,4	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XJ 2.0	Petrol	'15-	5,4	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XJ 3.0 V6	Petrol	'11-'12	6,5	M2C913-C	RAVENOL FDS SAE 5W-30		
XJ 3.0 V6 SC, 4WD	Petrol	'12-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
XJ 3.0 V6 SC, 4WD	Petrol	'15-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XJ 5.0 V8	Petrol	'09-'14	7,25	M2C925-A	RAVENOL SFE SAE 5W-20		
XJ 5.0 V8	Petrol	'09-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
XJ, XJR 5.0 V8	Petrol	'15-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
F-Type 3.0 V6	Petrol	'13-'13	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type 3.0 V6	Petrol	'14-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type 3.0 V6	Petrol	'15-'16	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
F-Type 3.0 V6	Petrol	'17-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type S 3.0 V6, AWD	Petrol	'13-'13	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
F-Type S 3.0 V6, AWD	Petrol	'14-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		

RAVENOL ECS SAE 0W-20

API SN/RCI ACEA A1/B1
Fully synthetic low friction motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, Resource Conserving, Ford WSS-M2C947-A, GM 6094M, Honda/Acura HTO-6, Chrysler MS-6395, Mitsubishi, Nissan, Mazda, Suzuki, Toyota, Jaguar Land Rover STJLR.51.5122

Art.Nr.: 1111102

RAVENOL VSF SAE 0W-30

ACEA C2
RAVENOL VSF SAE 0W-30 is a fully synthetic low friction engine oil based on PAO (Poly alpha olefines) with ClearSynto® technology for car diesel engines with and without turbocharging and direct injection. Minimizing friction, wear and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to the manufacturer's instructions.

Ford WSS-M2C950-A

Art.Nr.: 1111107

RAVENOL SFE SAE 5W-20

API SN/RCI
Fully synthetic low friction low SAPS motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, FORD WSS-M2C930-A, FORD WSS-M2C930-B (extended drain capability), Ford WSS-M2C925-A/B, Ford WSS-M2C948-B, Chrysler MS-6395, Honda/Acura HTO-6, Nissan, Mazda, Suzuki, Toyota, Fiat 9.55535-0R1, Jaguar Land Rover STJLR.03.5004

Art.Nr.: 1111110

RAVENOL FDS SAE 5W-30

API SL/CF ACEA A1/B1, A5/B5
Fully synthetic, low friction motor oil with ClearSynto® Technology for petrol and diesel passenger cars with and without turbocharging and direct injection.

Renault RN0700, FORD WSS-M2C913-D (fulfills FORD WSS-M2C913-A/B/C), Fiat 9.55535-G1, JAGUAR LAND ROVER STJLR.03.5003

Art.Nr.: 1111139

RAVENOL FLJ SAE 5W-30

ACEA C1
Synthetic, low SAPS, low-viscosity motor oil with ClearSynto® technology that is suitable for petrol and diesel cars, with or without turbochargers and fuel injectors. It minimises friction, deterioration and fuel consumption, as well as possessing excellent cold-start characteristics and a lengthened oil change interval.

JAGUAR LAND ROVER STJLR.03.5005, FORD WSS-M2C934-B, MAZDA, Mitsubishi

Art.Nr.: 1111143

MODEL	FUEL	MODEL YEAR	FILLING QUANTITY	SPECIFICATIONS APPROVED OIL TYPES	RAVENOL PRODUCT	RECOMMENDATION	ALTERNATIVES TO THE RAVENOL PRODUCT
F-Type S 3.0 V6, AWD	Petrol	'15-'16	7,25, 6,5	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
F-Type S 3.0 V6, AWD	Petrol	'17-	7,25, 6,5	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type S 5.0 V8	Petrol	'13-'13	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type S 5.0 V8	Petrol	'14-'14	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type R 5.0 V8, AWD	Petrol	'14-'16	6,5-7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Type SVR 5.0 V8 AWD	Petrol	'16-'16	6,5-7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
F-Type R, SVR 5.0 V8, AWD	Petrol	'17-	6,5-7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20	M2C925-A	RAVENOL SFE SAE 5W-20
F-Pace 3.0 V6	Petrol	'16-	6,5	STJLR.51.5122	RAVENOL ECS SAE 0W-20		
XKB 4.0 V8	Petrol	'96-'98	6,5-7,3		RAVENOL DXG SAE 5W-30		RAVENOL HCL SAE 5W-30
XKB 4.0 V8	Petrol	'98-'99	6,5-7,3	M2C913-B	RAVENOL FO SAE 5W-30		
XKB 4.0 V8	Petrol	'99-'03	6,5-7,3	M2C913-B	RAVENOL FO SAE 5W-30		
XKB 4.2	Petrol	'03-'06	7	M2C913-B	RAVENOL FO SAE 5W-30		
XKB 4.2	Petrol	'06-'09	7	M2C913-B	RAVENOL FO SAE 5W-30		
XKR	Petrol	'97-'98	6,5-7,3	M2C913-B	RAVENOL FO SAE 5W-30		
XKR	Petrol	'98-'99	6,5-7,3	M2C913-B	RAVENOL FO SAE 5W-30		
XKR	Petrol	'99-'03	6,5-7,3	M2C913-B	RAVENOL FO SAE 5W-30		
XKR	Petrol	'03-'06	7	M2C913-B	RAVENOL FO SAE 5W-30		
XK 3.5 V8	Petrol	'07-'09	6	M2C913-B	RAVENOL FO SAE 5W-30		
XK 4.2 V8, XKR SC	Petrol	'06-'09	7	STJLR.03.5003	RAVENOL FDS SAE 5W-30	STJLR.03.5003	RAVENOL FO SAE 5W-30
XK 5.0 V8	Petrol	'09-'13	7,25	M2C925-A	RAVENOL SFE SAE 5W-20		
XKR 5.0 V8-, XKR-S 5.0 V8 SC	Petrol	'09-'13	7,25	M2C925-A	RAVENOL SFE SAE 5W-20		
XK-, XKR 5.0 V8-, XKR-S 5.0 V8 SC	Petrol	'14-	7,25	STJLR.51.5122	RAVENOL ECS SAE 0W-20		

RAVENOL ECS SAE 0W-20

API SN/RC ACEA A1/B1
Fully synthetic low friction motor oil with ClearSyntho® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, Resources Conserving, Ford WSS-M2C947-A, GM 6094M, Honda/Acura HTO-6, Chrysler MS-6395, Mitsubishi, Nissan, Mazda, Suzuki, Toyota, Jaguar Land Rover STJLR.51.5122

Art.Nr.: 1111102

RAVENOL VSF SAE 0W-30

ACEA C2
RAVENOL VSF SAE 0W-30 is a fully synthetic low friction engine oil based on PAO (Poly alpha olefines) with ClearSyntho® technology for car diesel engines with and without turbocharging and direct injection. Minimizing friction, wear and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to the manufacturer's instructions.

Ford WSS-M2C950-A

Art.Nr.: 1111107

RAVENOL SFE SAE 5W-20

API SN/RC
Fully synthetic low friction low SAPS motor oil with ClearSyntho® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, FORD WSS-M2C930-A, FORD WSS-M2C930-B (extended drain capability), Ford WSS-M2C925-A/B, Ford WSS-M2C948-B, Chrysler MS-6395, Honda/Acura HTO-6, Nissan, Mazda, Suzuki, Toyota, Fiat 9.55535-CR1, Jaguar/LandRover STJLR.03.5004

Art.Nr.: 1111110

RAVENOL FDS SAE 5W-30

API SL/CF ACEA A1/B1, A5/B5
Fully synthetic, low friction motor oil with ClearSyntho® Technology for petrol and diesel passenger cars with and without turbo-charging and direct injection.

Renault RN0700, FORD WSS-M2C913-D (fulfills FORD WSS-M2C913-A/B/C), Fiat 9.55535-G1, JAGUAR LAND ROVER STJLR.03.5003

Art.Nr.: 1111139

RAVENOL FLJ SAE 5W-30

ACEA C1
Synthetic, low SAPS, low viscosity motor oil with ClearSyntho® technology that is suitable for petrol and diesel cars, with or without turbochargers and fuel injectors. It minimises friction, deterioration and fuel consumption, as well as possessing excellent cold-start characteristics and a lengthened oil change interval.

JAGUAR LAND ROVER STJLR.03.5005, FORD WSS-M2C934-B, MAZDA, Mitsubishi

Art.Nr.: 1111143

MODEL	FUEL	MODEL YEAR	FILLING QUANTITY	SPECIFICATIONS APPROVED OIL TYPES	RAVENOL PRODUCT	RECOMMENDATION	ALTERNATIVES TO THE RAVENOL PRODUCT
X-type 2.0D	Diesel	'03-'09	6,7	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
X-type 2.2D	Diesel	'05-'10	6,7	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
S-type 2.7D	Diesel	'04-'07	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XE 2.0D, 2.0D AWD	Diesel	'15-	6,52	STJLR.03.5007	SPECIAL PRODUCT		
XF 2.0D, 2.0D AWD	Diesel	'15-	6,52	STJLR.03.5007	SPECIAL PRODUCT		
XF 2.2D TD4	Diesel	'12-'15	5,86	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XF 2.2D TD4 DPF	Diesel	'12-'15	5,86	M2C934-B	RAVENOL FLJ SAE 5W-30	ACEA C2	RAVENOL FEL SAE 5W-30
XF 2.7D V6	Diesel	'08-'09	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XF 3.0D V6, 3.0D V6 S	Diesel	'09-'12	6,5-6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		
XF 3.0D V6, 3.0D V6 S	Diesel	'12-'15	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XF 3.0D V6 DPF, 3.0D V6 S DPF	Diesel	'12-'15	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		RAVENOL FEL SAE 5W-30
XF 3.0D TDV6	Diesel	'15-	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XF 3.0D TDV6 DPF	Diesel	'15-	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		
XJ 6 2.7D	Diesel	'05-'09	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XJ 3.0D	Diesel	'09-'10	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XJ 3.0D DPF	Diesel	'09-'10	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		
XJ 3.0D	Diesel	'10-'15	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XJ 3.0D DPF	Diesel	'10-'15	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		
XJ 3.0D	Diesel	'15-	6,6	M2C913-B	RAVENOL FDS SAE 5W-30	M2C913-B	RAVENOL FO SAE 5W-30
XJ 3.0D DPF	Diesel	'15-	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		
F-Pace 2.0D, AWD	Diesel	'16-	6,5	STJLR.03.5007	SPECIAL PRODUCT		
F-Pace 3.0D	Diesel	'16-	6,6	M2C934-B	RAVENOL FLJ SAE 5W-30		



RAVENOL ECS SAE 0W-20

API SN/RCI ACEA A1/B1
Fully synthetic low friction motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, Resource Conserving, Ford WSS-M2C947-A, GM 6094M, Honda/Acura HTO-6, Chrysler MS-6395, Mitsubishi, Nissan, Mazda, Suzuki, Toyota, Jaguar Land Rover STJLR.51.5122

Art.Nr.: 1111102



RAVENOL VSF SAE 0W-30

ACEA C2
RAVENOL VSF SAE 0W-30 is a fully synthetic low friction engine oil based on PAD (Poly alpha olefines) with ClearSynto® technology for car diesel engines with and without turbocharging and direct injection. Minimizing friction, wear and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to the manufacturer's instructions.

Ford WSS-M2C950-A

Art.Nr.: 1111107



RAVENOL SFE SAE 5W-20

API SN/RCI
Fully synthetic low friction low SAPS motor oil with ClearSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

ILSAC GF-5, FORD WSS-M2C930-A, FORD WSS-M2C930-B (extended drain capability), Ford WSS-M2C925-A/B, Ford WSS-M2C948-B, Chrysler MS-6395, Honda/Acura HTO-6, Nissan, Mazda, Suzuki, Toyota, Fiat 9.55535-CR1, JaguarLandRover STJLR.03.5004

Art.Nr.: 1111110



RAVENOL FDS SAE 5W-30

API SL/CF ACEA A1/B1, A5/B5
Fully synthetic, low friction motor oil with ClearSynto® Technology for petrol and diesel passenger cars with and without turbocharging and direct injection.

Renault RN0700, FORD WSS-M2C913-D (fulfills FORD WSS-M2C913-A/B/C), Fiat 9.55535-G1, JAGUAR LAND ROVER STJLR.03.5003

Art.Nr.: 1111139



RAVENOL FLJ SAE 5W-30

ACEA C1
Synthetic, low SAPS, low-viscosity motor oil with ClearSynto® technology that is suitable for petrol and diesel cars, with or without turbochargers and fuel injectors. It minimises friction, deterioration and fuel consumption, as well as possessing excellent cold-start characteristics and a lengthened oil change interval.

JAGUAR LAND ROVER STJLR.03.5005, FORD WSS-M2C934-B, MAZDA, Mitsubishi

Art.Nr.: 1111143